



25-Lb Handi-Pak Spools

Product Description

Nehring offers a DSA "Utility Grade" Bare Copper that has 15% greater elongation than standard soft drawn bare copper. We require a minimum of 35% elongation over the 30% required by ASTM. Our "Utility Grade" copper offers greater flexibility making it easier for linemen to tie down insulators on a hot line.

Application

Product Data

Soft Drawn Bare Copper 25 Pound Handi-Pak

Size (AWG)	Stranding	Spool Length(feet per 25 lbs.)
18	Solid	5,081
16	Solid	3,200
14	Solid	2,015
12	Solid	1,265
10	Solid	795
8	Solid	500
6	Solid	315
4	Solid	198
2	Solid	125
8	7/w	490
6	7/w	308
4	7/w	194
2	7/w	122

Utility Grade - Dead-Soft Annealed Bare Copper

Size (AWG)	Diameter (inches)	Spool Length (feet per 25 lbs.)	Minimum Elongation
6	.1620	315	35%
4	.2043	198	35%

*Manufactured with pride in DeKalb, IL USA.

Specification Data

Source URL: <http://www.nehringwire.com/copper/dsa-utility-grade-copper/25-lb-handi-pak-spools>
 Published on *Nehring Electrical Work Company* (<http://www.nehringwire.com>)